


Data sheet

ID	HFPRM Turbo BK
Description	rigid insulating conduit with sectional corrugation, halogenfree, plain, with moulded-on coupler
Properties	medium compression resistance, medium impact resistance
Colour	black, similar to RAL 9005
Fire Behaviour	non flame propagating
Classification	33431



Norms: EN 61386-1, EN 61386-21

halogenfrei according to DIN VDE 0604
halogenfree according to EN 50642
halogenfree according to EN 60754



Compressive strength	Impact strength	Operating temperature	Bending strength	UV-Level*
Medium (class 3)	Medium (class 3)	-25 to +105 °C	Rigid	L2

Art. no.	Outer diameter	di	ps	pl
087 219	16 mm	12,2 mm	3 m	111 m
087 220	20 mm	15,4 mm	3 m	111 m
087 221	25 mm	19,8 mm	3 m	57 m
087 222	32 mm	26,7 mm	3 m	57 m
098 781	40 mm	34,1 mm	3 m	21 m
098 782	50 mm	43,5 mm	3 m	21 m
098 783	63 mm	56,5 mm	3 m	21 m

Areas of Recommended Application

Area	
Flush mounted (plaster)	True
Surface mounted	True
Suitable for concrete installation	True
Machine and systems installation	True
Suitable for subsurface installation (screed))	True
Outdoor installation	True
Suitable for installation on wood	True
Hollow wall	True
Underground installation	True

Further technical details

Details	
Halogen free	True
High conducting inner coating	True
With sleeve	True
Fire retardant version	True
Material	PP-Blend

*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.