


LOOSE-TUBE CABLES

Loose-tube cables are available in unitube or multi-loose-tube constructions. Multi-loose-tube cables are available in variations up to 216 fibres. The three standard constructions are a general duct-grade cable, a glass yarn armoured cable, and a corrugated-steel-tape armoured direct-burial cable. There are two sheath options: Polyethylene for external applications, and Low-Smoke Halogen Free (LSHF/LSZH) for universal or internal applications.

Loose-tube cables are designed for use in building or campus backbone applications and can be installed by blowing, winching, or pulling into existing sub ducts or cable conduits. External steel-tape armoured products can also be direct buried. Bespoke loose-tube cables to client specifications with additional features or modified mechanical performance are available on request subject to MOQ and lead-time.




MINI UNITUBE CABLE

- For short-run backbone applications
- Lightweight, flexible, and compact
- Uses white sheath to be discrete in the home
- 2- and 4-fibre options constructed around a 1.9 mm gel-filled loose tube, layer of glass yarns, and a Low-Smoke Halogen-Free (LSHF/LSZH) outer sheath

[A] MINI UNITUBE CABLES (EUROCLASS ECA)

DESCRIPTION	OM1	OM2	OM3	OM4	SINGLE-MODE
2-Fibre	HF062UNI1902LU-Eca	HF050UNI1902LU-Eca	HFOM3UNI1902LU-Eca	HFOM4UNI1902LU-Eca	HF008UNI1902LU-Eca
4-Fibre	HF062UNI1904LU-Eca	HF050UNI1904LU-Eca	HFOM3UNI1904LU-Eca	HFOM4UNI1904LU-Eca	HF008UNI1904LU-Eca



DUCT-GRADE UNITUBE CABLES

- Ideal for LAN backbones, telecom access line, campus networks, and FTTH drops
- Lightweight, compact design
- 4-12 fibre options constructed around a 2.90 mm gel-filled loose tube
- 16-24 fibre variants use a 4.00 mm loose tube
- Cable colour is black

[B] DUCT-GRADE UNITUBE CABLES

UNIVERSAL	LEVITON PART NO.	BRAND-REX PART NO.
OM1, LSHF/LSZH, EuroClass Dca	—	GF062UNlxxLU-Dca
OM1, LSHF/LSZH, EuroClass Eca	—	GF062UNlxxLU-Eca
OM2, LSHF/LSZH, EuroClass Dca	—	GF050UNlxxLU-Dca
OM2, LSHF/LSZH, EuroClass Eca	121-50LRZ-xx2	GF050UNlxxLU-Eca
OM3, LSHF/LSZH, EuroClass Dca	—	GFOM3UNlxxLU-Dca
OM3, LSHF/LSZH, EuroClass Eca	121-5LLRZ-xx2	GFOM3UNlxxLU-Eca
OM4, LSHF/LSZH, EuroClass Dca	—	GFOM4UNlxxLU-Dca
OM4, LSHF/LSZH, EuroClass Eca	121-55LRZ-xx2	GFOM4UNlxxLU-Eca
Single-Mode, LSHF/LSZH, EuroClass Dca	—	GF008UNlxxLU-Dca
Single-Mode, LSHF/LSZH, EuroClass Eca	121-SMLRZ-xx2	GF008UNlxxLU-Eca
EXTERNAL		BRAND-REX PART NO.
OM1		GF062UNlxxNM
OM2		GF050UNlxxNM
OM3		GFOM3UNlxxNM
OM4		GFOM4UNlxxNM
Single-Mode		GF008UNlxxNM

xx = Fibre Count: 04, 06, 08, 12, 16 (2 x bundles), or 24 (2 x bundles)

Brand-Rex is a subsidiary of Leviton Mfg. Co., Inc