

For more Information
please call

1-800-Belden1



General Description:

20 AWG stranded (19x33) .035" tinned copper conductor, polyethylene insulation, tinned copper braid shield (95% coverage), non-contaminating PVC jacket.

Physical Characteristics (Overall)

Conductor

AWG:

| # Coax | AWG | Stranding | Conductor Material | Dia. (mm) |
|--------|-----|-----------|--------------------|-----------|
| 1 | 20 | 19x33 | TC - Tinned Copper | 0.889 |

Total Number of Conductors: 1

Insulation

Insulation Material:

| Insulation Material | Dia. (mm) |
|---------------------|-----------|
| PE - Polyethylene | 2.921 |

Outer Shield

Outer Shield Material:

| Type | Outer Shield Material | Coverage (%) |
|-------|-----------------------|--------------|
| Braid | TC - Tinned Copper | 95 |

Outer Jacket

Outer Jacket Material:

| Outer Jacket Material |
|--|
| PVCNC - Polyvinyl Chloride Non-Contaminating |

Overall Cable

Overall Nominal Diameter: 4.953 mm

Mechanical Characteristics (Overall)

Operating Temperature Range: -40°C To +85°C

UL Temperature Rating: 85°C

Bulk Cable Weight: 35.717 Kg/Km

Max. Recommended Pulling Tension: 186.824 N

Min. Bend Radius/Minor Axis: 50.800 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 10/01/2005

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

Detailed Specifications & Technical Data



METRIC MEASUREMENT VERSION

8262 Coax - 50 Ohm Coax

| | |
|-----------------------------------|-------------------------|
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |
| Military Specification: | MIL-C-17, M17/155-00001 |
| RG Type: | 58C/U |

Plenum/Non-Plenum

| | |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

Impedance (Ohm)

50

Nom. Inductance:

Inductance (µH/m)

0.252637

Nom. Capacitance Conductor to Shield:

Capacitance (pF/m)

101.055

Nominal Velocity of Propagation:

VP (%)

66

Nominal Delay:

Delay (ns/m)

5.05274

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)

35.4348

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)

13.4521

Nom. Attenuation:

| Freq. (MHz) | Attenuation (dB/100m) |
|-------------|-----------------------|
| 1 | 1.3124 |
| 10 | 4.5934 |
| 50 | 10.8273 |
| 100 | 16.0769 |
| 200 | 23.9513 |
| 400 | 37.7315 |
| 700 | 55.777 |
| 900 | 65.62 |
| 1000 | 70.5415 |

Max. Operating Voltage - Non-UL:

Voltage

1400 V RMS

Notes (Overall)

Notes: Non-SWR swept version of RG-58.

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|---------------|----------|-------------|-------|-------|--------------------|
| 8262 010U1000 | 1,000 FT | 26.000 LB | BLACK | | M17/155-00001 COAX |
| 8262 010U500 | 500 FT | 13.500 LB | BLACK | | M17/155-00001 COAX |
| 8262 0101000 | 1,000 FT | 27.000 LB | BLACK | C | M17/155-00001 COAX |

METRIC MEASUREMENT VERSION

8262 Coax - 50 Ohm Coax

| | | | | | |
|-------------|--------|-----------|-------|---|--------------------|
| 8262 010500 | 500 FT | 14.000 LB | BLACK | C | M17/155-00001 COAX |
|-------------|--------|-----------|-------|---|--------------------|

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 3 Revision Date: 03-30-2012

© 2019 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).