


**KSB, násuvné koleno s rozšířeným hrdlem;** černé (RAL 9005), pro pískotěsné spojení KSR nebo BR trubek

**KSB, nasúvacie koleno s rozšíreným hrdlom;** čierne (RAL 9005), pre piesko-tesné spojenie KSR, alebo BR rúr




<b>materiál</b>	PVC-U	<b>tepl. rozsah</b>	-5 °C/+60 °C
-----------------	-------	---------------------	--------------




**úhel 30°**  
**uhol 30°**

typ	dn	r [mm]	mb	ref. č.
KSB 50/30°	50,0	270,0	65	001 820
KSB 63/30°	63,0	330,0	30	001 821
KSB 75/30°	75,0	405,0	15	001 822
KSB 90/30°	90,0	495,0	12	001 823
KSB 110/30°	110,0	605,0	1	001 824
KSB 125/30°	125,0	730,0	1	001 825
KSB 140/30°	140,0	875,0	1	001 826
KSB 160/30°	160,0	1035,0	1	001 827



**úhel 45°**  
**uhol 45°**

typ	dn	r [mm]	mb	ref. č.
KSB 50/45°	50,0	270,0	50	001 836
KSB 63/45°	63,0	330,0	24	001 837
KSB 75/45°	75,0	405,0	12	001 838
KSB 90/45°	90,0	495,0	3	001 839
KSB 110/45°	110,0	605,0	1	001 840
KSB 125/45°	125,0	730,0	1	001 841
KSB 140/45°	140,0	875,0	1	001 842
KSB 160/45°	160,0	1035,0	1	001 843



**úhel 90°**  
**uhol 90°**

typ	dn	r [mm]	mb	ref. č.
KSB 50/90°	50,0	270,0	20	001 852
KSB 63/90°	63,0	330,0	5	001 853
KSB 75/90°	75,0	405,0	3	001 854
KSB 90/90°	90,0	495,0	3	001 855
KSB 110/90°	110,0	605,0	1	001 856
KSB 125/90°	125,0	730,0	1	001 857
KSB 140/90°	140,0	875,0	1	001 858
KSB 160/90°	160,0	1035,0	1	001 859