

outTEG II DOUBLE NATURAL



Don't compromise. You can benefit from the advantages offered by the new specialized outTEG line. With a compact design, clear line and climate control system, outTEG satisfies the requirements of customers based in high temperature locations as well as those situated in regions with extremely low temperatures.

MAIN ADVATAGES

- Features integrated roof and plinth
- Welded stainless steel enclosure frame
- All removable parts are made of aluminum
- Compact design = no point of access for lever-type tools
- Ready for crane transport

COLOR SAMPLER:  RAL 7035

 RAL 7046

DESCRIPTION:

Material

- Door, rear panel, roof - 2 mm AlMg3
- Frame, plinth - 2 mm stainless steel 1.4016 (AISI 403)

Color

- Body color RAL 7035 (light grey, with UV protection for outdoor use)
- Roof and plinth color - RAL 7046 (dark grey, with UV protection for outdoor use)

IP rating

- IP65 according to EN 60529 (Degree of IP rating can be reduced after mounting some accessories)

Seismic protection

- Seismic approvals according to Bellcore GR-63-CORE Zone 3 (Zone 4 upon request)

Package includes

- Double-walled outdoor cabinet, fully mounted
- Ventilation - natural air flow between inner and outer walls

- Removable rear panel
- Removable roof
- Front door with multi-point locking system, key combination 333, door stop. Easily configured to a right or left hand door mounting
- 100 mm plinth
- Vertically mount the internal rails with 25 mm perforations
- Removable gland plate
- Eye-bolts
- Side panels (see page 10)

For detailed information see page 48

OUTTEG DOUBLE-WALLED, SINGLE DOOR, HEIGHT 600 AND 1200 mm

H (U)	Package	12 U	16 U	21 U	21 U	25 U	25 U
H (mm)		600	800	1000	1000	1200	1200
W (mm)		650	650	650	800	800	1000
D (mm)		600	600	600	500	800	700
Weight (kg)		63	69	81	82	115	119
Code	1 pc	OMR-DN-066506-R	OMR-DN-086506-R	OMR-DN-106506-R	OMR-DN-100805-R	OMR-DN-120808-R	OMR-DN-121007-R
ACCESSORIES							
Side panel**	1 pc	OMR-DN-S0606-1	OMR-DN-S0806-1	OMR-DN-S1006-1	OMR-DN-S1005-1	OMR-DN-S1208-1	OMR-DN-S1207-1
Mounting plate, full installation	1 pc	IDO-MM-F665	IDO-MM-F865	IDO-MM-F1065	IDO-MM-F108	IDO-MM-F128	IDO-MM-F1210
19" and 21" vertical rails	1 pair	IDO-MR-V6	IDO-MR-V8	IDO-MR-V10	IDO-MR-V10	IDO-MR-V12	IDO-MR-V12
ETSI vertical rails	1 pair	IDO-MR-E6	IDO-MR-E8	IDO-MR-E10	IDO-MR-E10	IDO-MR-E12	IDO-MR-E12
N profile for vertical rails	1 pair	IDO-MR-N6*	IDO-MR-N6*	IDO-MR-N6*	IDO-MR-N5*	IDO-MR-N8*	-
L profile for vertical rails	1 set	-	-	-	IDO-MR-L5	IDO-MR-L8	IDO-MR-L7
Horizontal rail	1 pair	see page 16					
Baying kit	1 set	OMR-DN-K0606	OMR-DN-K0806	OMR-DN-K1006	OMR-DN-K1005	OMR-DN-K1208	OMR-DN-K1207
Fixing frame for a concrete base	1 pc	IDO-MF-P6506	IDO-MF-P6506	IDO-MF-P6506	IDO-MF-P0805	IDO-MF-P0808	IDO-MF-P1007

* You have to order 2 sets, for a height of 1400 and 1600 mm 3 sets must be ordered. For 800 mm width cabinets with IDO-MR-Nxx, an IDO-MR-N-B holder (2 sets for 1 set of IDO-MR-Nxx) must be ordered as well.

** You have to order 2 pcs

OUTTEG DOUBLE-WALLED, SINGLE DOOR, HEIGHT 1400 AND 1600 mm						
H (U)	Package	30 U	34 U	34 U	34 U	34 U
H (mm)		1400	1600	1600	1600	1600
W (mm)		650	650	800	800	1000
D (mm)		600	400	700	1000	800
Code	1 pc	OMR-DN-146506-R	OMR-DN-166504-R	OMR-DN-160807-R	OMR-DN-160810-R	OMR-DN-161008-R
ACCESSORIES						
Side panel**	1 set	OMR-DN-S1406-1	OMR-DN-S1604-1	OMR-DN-S1607-1	OMR-DN-S1610-1	OMR-DN-S1608-1
Mounting plate, full installation	1 pc	IDO-MM-F1465	IDO-MM-F1665	IDO-MM-F168	IDO-MM-F168	IDO-MM-F1610
19" and 21" vertical rails	1 pair	IDO-MR-V14	IDO-MR-V116	IDO-MR-V16	IDO-MR-V16	IDO-MR-V16
ETSI vertical rails	1 pair	IDO-MR-E14	IDO-MR-E16	IDO-MR-E16	IDO-MR-E16	IDO-MR-E16
N profile for vertical rails	1 pair	IDO-MR-N6*	IDO-MR-N4*	IDO-MR-N7*	IDO-MR-N10*	–
L profile for vertical rails	1 set	–	–	IDO-MR-L7	IDO-MR-L10	IDO-MR-L8
Horizontal rail	1 pair	see page 16				
Baying kit	1 set	OMR-DN-K1406	OMR-DN-K1604	OMR-DN-K1607	OMR-DN-K1610	OMR-DN-K1608
Fixing frame for concrete base	1 pc	IDO-MF-P6506	IDO-MF-P6504	IDO-MF-P0807	IDO-MF-P0810	IDO-MF-P1008

* You have to order 2 sets, for a height of 1400 and 1600 mm height 3 sets must be ordered. For 800 mm width cabinets with IDO-MR-Nxx, an IDO-MR-N-B holder (2 sets for 1 set

of IDO-MR-Nxx) must be ordered as well.

** You have to order 2 pcs

Do you need a solution for pole installation? Use outTEG LITE



For more information, please visit **page 22** or contact our technical team at www.conteg.com/contacts