

# Class E<sub>A</sub> / Cat. 6<sub>A</sub> - shielded

## Patch Cords

### RJ45 Cat. 6/E<sub>A</sub> 500 MHz, screened, wiring 1:1

with uninet 7702 flex 4P Cat.7  
suitable for 1GBase-T and 10GBase-T transmission

- Cu-Patch cords Cat. 6/E<sub>A</sub> (4x2xAWG26)  
for structured premises cabling
- Applicable standards: EN 50173-1:2002, ISO/IEC 11801:2002/A2:2010
- Customized adjustments (bend limiting boot, termination, label)  
are available at short notice



Length/Meter	unilan® Patch Cord RJ45 Cat.6/E <sub>A</sub> screened, wiring 1:1 (mit uninet® 7702 flex 4P FRNC/LSOH Cat.7)					
	grey	green	yellow	red	blue	orange
0,5	653 503	653 553	653 603	653 653	653 703	653 753
1,0	653 508	653 558	653 608	653 658	653 708	653 758
1,5	653 509	653 559	653 609	653 659	653 709	653 759
2,0	653 510	653 560	653 610	653 660	653 710	653 760
2,5	653 511	653 561	653 611	653 661	653 711	653 761
3,0	653 512	653 562	653 612	653 662	653 712	653 762
4,0	653 514	653 564	653 614	653 664	653 714	653 764
5,0	653 516	653 566	653 616	653 666	653 716	653 766
6,0	653 518	653 568	653 618	653 668	653 718	653 768
7,0	653 520	653 570	653 620	653 670	653 720	653 770
8,0	653 522	653 572	653 622	653 672	653 722	653 772
9,0	653 524	653 574	653 624	653 674	653 724	653 774
10,0	653 526	653 576	653 626	653 676	653 726	653 776
12,5	653 527	653 577	653 627	653 677	653 727	653 777
15,0	653 528	653 578	653 628	653 678	653 728	653 778
20,0	653 530	653 580	653 630	653 680	653 730	653 780